THE BANK OF MYSORE, LIMITED, BANGALORE.

Statement of the affairs of the Bank of Mysore, Limited, for the week ending 14th May 1936, published under Article 141 of the Articles of Association.

LIABILITIES		ASSETS	
	Rs.		Rs.
To Capital Receipts	20,00,000	By Cash in Hand and at Bankers ..	30,59,716
,, Reserve Fund	24,25,000	,, Loans and Cash Credit Accounts	162,65,566
,, Public and other Deposits ..	225,91,064	,, Bills discounted	7,75,923
,, Sundries	4,59,171	,, Investments	65,98,696
		,, Balance at Agencies	53,033
(Annas and pies omitted.)		,, Dead Stock	5,97,410
		,, Sundries	1,24,891
Total ..	274,75,235	Total ..	274,75,235

BANGALORE,
Dated 18th May 1936.

M. H. DASTUR,
Offg. *Manager.*

I intend moving the Hon'ble the High Court of Mysore, for my enrolment as an Advocate thereof.

M. N. SRINIVASAN, B.Sc. (Hons.), LL.B.

UNIVERSITY OF MYSORE.

Notification No. 22817, *dated the 16th May* 1936.

Mr. N. Kasturi Iyer, M.A., B.L., Lecturer in History, Maharaja's College, Mysore, is permitted to change his name to "N. Kasturi."

(General Secretary's letter No. E. 3104—Uni. 105-35-2, dated the 9th May 1936.)

By Order,
V. GOPALASWAMI AIENGAR,
Registrar.

GOVERNMENT OF MYSORE, STORES PURCHASE COMMITTEE, BANGALORE.

No. S. P. C. 18990-19002, *dated* 18*th May* 1936.

To

The Firms dealing in Pumping Sets.

Enquiry No. 1823.

ELECTRIC PUMPING SET FOR MANDYA WATER WORKS.

GENTLEMEN,

Please be good enough to intimate your best price and the earliest time of delivery for one electric pumping set described in the undermentioned schedule.

In should be distinctly understood that the acceptance by us of your quotation will be subject to the following conditions :—

Withdrawal from the quotation after it is accepted or failure to make the supply within the specified time or according to specifications will entail cancellation of the order and purchases being made at your expense from other sources in addition to the levy of a penalty of 3 per cent of the value of the order as and by way of liquidated damages. In such an event, the Stores Purchase Committee reserve the right to remove your name from the list of approved firms.

The quotations should be superscribed "Quotations for Electric Pumping Set for Mandya Water Works," with the above Enquiry Number.

This enquiry will be closed on the 5th June 1936.

Schedule.

Specification for the Electric Pumping Set required for Mandya Water Works.

The pumping set should consist of one electric motor directly coupled on to a centrifugal pump on a common bed plate, by means of a flexible coupling. The capacity of the pump should be about 160 gallons per minute against 100 ft. head.

Motor.—The motor should be suitable for 220 volts, 25 cycle, 3 phase A.C.

It should be drip proof and suited for this tropical country. There must be sufficient H.P. in reserve so that the same may not be overloaded.

The motor should also be equipped with suitable starter also.

Pump.—The pump should be single stage with horizontally split casing and should have ball or roller bearings.

The glands must be split and suitable sleeves should be provided for at the glands. It should deliver 160 gallons per minute against 100 ft. head from all causes.

The pump should have phosper bronze impellers with renewable neck rings and the shaft should be with stainless steel.

The motor and pump should be fixed on C.I. bed plate which should be sufficiently heavy and strong. Both motor and pump should be correctly aligned and necessary dowels have to be fixed both on the motor and pump after correct alignment so that the same may not be altered.

The coupling should be of flexible type with rubber washers. One set of spare rubber washers should be provided for in the quotation.

Necessary air escape cocks, charging bowls, etc., with the following accessories should also be provided for :—

(1) One foot valve of the latest type suitable to the pump.
(2) One delivery valve with hand wheel.
(3) One reflux valve.
(4) One 6" pressure guage with....feet reading up to 200 ft.

The pumping set should be complete with foundation bolts, necessary working drawing and instruction book, etc.

No. S. P. C. 19039-43, *dated* 18*th May* 1936.

To

The Firms dealing in Steel Racks.

Enquiry No. 1825.

STEEL RACKS FOR THE STATE LIFE INSURANCE OFFICE.

DEAR SIR—GENTLEMEN,

Please be good enough to intimate your best prices and the earliest time of delivery for the materials described in the schedule printed below.

It should be distinctly understood that the acceptance by us of your quotation will be subject to the following conditions :—

Withdrawal from the quotation after it is accepted or failure to make the supply within the specified time or according to specifications will entail cancellations of the order and purchases being made at your expense from other sources in addition to the levy of a penalty of 3 per cent of the value of the order as and by way of liquidated damages. In such an event, the Stores Purchase Committee reserve the right to remove your name from the list of approved firms.

The quotations should be superscribed "Quotations for Steel Racks to the State Life Insurance Office," with the above enquiry number.

This enquiry will be closed on the 30th May 1936.

Schedule.

Item No.	Description of material offered	Quantity	Price quoted	Time of delivery
1	Open type steel record racks as per following specification :— $5\frac{1}{2}' \times 3' \times 15''$ with five shelves. The racks should be made of strong angle steel of size $1\frac{1}{2}'' \times 1\frac{1}{2}'' \times \frac{1}{8}''$ and the partitions should be made of best mild steel sheets of 1/16" thick. Four holes to be made on both sides of each of the partition sheets and		for free delivery in Bangalore.	

Item No.	Description of material offered	Quantity	Price quoted	Time of delivery
	should be neatly painted with olive green ..	Three		
2	Steel racks of the following specification :— (1) The racks are required to be fitted back to back to the existing racks. (2) Height 8′ 4″; width 3′; depth 19″ with 11 shelves including top and bottom (8 in the bottom and 3 in the top). (3) The top shelves are also to be provided with separate shutters as in the existing ones. (4) The racks are to be provided with cornices and top plates. (5) The racks are to be painted olive green. (6) The bolts, nuts, etc., used for purposes of rivetting should be of a uniform and standard pattern. (7) The quality and temper of steel should be similar to the existing racks in the Insurance Office. (8) The racks are to be fitted free of cost in the Office. (9) The racks are to be suitably provided with punches for adjustment of shelves	Three		

N.B.—Sample racks may be seen in the Office of the Secretary, Mysore State Life Insurance Committee, Bangalore, on working days between 11 A.M. and 5 P.M.

No. S. P. C. 19003-24, *dated* 18*th May* 1936.

To

The Firms dealing in Pumping Sets.

Enquiry No. 1827.

ELECTRIC PUMPING SET FOR NANJUNGUD WATER WORKS.

GENTLEMEN,

Please be good enough to intimate your best prices and earliest time of delivery for one Electric Pumping Set described in the schedule printed below.

It should be distinctly understood that the acceptance by us of your quotation will be subject to the following conditions :—

Withdrawal from the quotation after it is accepted or failure to make the supply within the specified time or according to specifications will entail cancellation of the order and purchases being made at your expense from other sources in addition to the levy of a penalty of 3 per cent of the value of the order as and by way of liquidated damages. In such an event the Stores Purchase Committee reserve the right to remove your name from the list of approved firms.

The quotations should be supercribed " Quotations for Electric Pumping Set for Nanjungud Water Works ", with the above enquiry Number.

This enquiry will be closed on the 5th June 1936.

SCHEDULE.

Specifications for A. C. Motor Driven Centrifugal Low Lift Pump required for Pumping Water from the river to the Settling Tank at Nanjangud.

Pump.—One centrifugal low lift pump capable of giving a discharge of about 250 gallons per minute against a total head of 60 ft. from all causes.

The pump should be made of hard grained cast iron casing and fitted with phosphor-bronze impeller and neck rings and bushes mounted on stainless steel shaft working in ball bearing at the ends.

The pump should be further fitted with pressure and vacuum gauges, priming tundish, drain cock, etc.

The pump should be of horizontally split casing type to enable easy dismantling for inspection and overhualing.

The pump is to be supplied with a footvalve and strainer suited to the suction diameter of the pump and the delivery side of it to be fitted with a non-return valve and a sluice valve suited to its delivery size. The water to be pumped is raw water direct from the river.

Motor.—The pump is to be driven by a suitable electric motor running on 220 volts, 3 phase, 25 cycle A. C. system.

The motor to have drip-proof casing working on ball bearings and provided with ample ventilation as it is to work at a temperature of about 100° F.

The motor and pump are to be mounted on a common base-plate and to be directly coupled by means of flexible couplings and bushes.

The above motor driven unit to be supplied with suitable starting switch board, and panel fitted with volt meter and ammeter.

SPARES.—

Pump.—One set of neck-rings, bushes.
One set of two bearings.
One impeller.

Motor.—One set of bearings.

Yours faithfully,
V. VEDAVYASACHARYA,
Secretary,
Stores Purchase Committee.